

Nouzová

Nouzová tabulka jednostranná, 3h, autotest, 5000K, 1W

Kod: VRL-EPE-EX3-AT-3h

Cena: Cena na dotaz

Poptávka



Prohlédnout v katalogu



W Výkon

-

K CCT

6000K/Ra>80

Ra CRI

-

IP Krytí

IP20

A Optika

-



Popis produktu

Nouzová tabulka jednostranná, 3h, autotest, 5000K, 1W je skladová varianta zařazená do katalogu Veralight. Název, výkonové a barevné provedení vycházejí z evidenční tabulky; konstrukční a rodinné parametry jsou převzaté z ověřené zdrojové stránky výrobce. Produkt je vhodné finálně vybírat podle konkrétního projektu, montáže a požadovaných světelných parametrů. Products Products Series LED Emergency Downlight Emergency Tracklight LED Emergency Drivers

Technicke parametry

Model	EPE-EX6	EPA-EX6
Voltage	220-240VAC, 50/60Hz	220-240VAC, 50/60Hz
Mains Power	3W Max	3W Max
Emergency Power	1W Max	1W Max
Battery	Li-ion 3. 7V1200mAh/LiFePO43.2V 1500mAh	LiFePO43.2V1500mAh
Charge Time	>=24H	>=16H
Discharge Duration	>=3H	>=2H
CCT/CRI	6000K/Ra>80	6000K/Ra>80
Visibility	30M	24M
Test Mode	AT/MT/DALI	AT/MT/DALI
Protection Class	Class II	Class II
IP Rating	IP20	IP20

Galerie produktu

